



ARAI Certificate

Comes with ARAI (Automotive Research Association of India) Certificate



SOS Button

Comes with an SOS button that can be used in emergency situation



Operating Voltage

Comes with a wide operating voltage of input range from 9V to 36V



90 Days Data Backup

With 90 days data backup user can check all past reports and playback in ease



Water Resistant Design

Device comes with a water resistance casing design to prevent water entering the device



Multiple Reports

Many useful reports like distance traveled, ignition ON/OFF, Stoppage report, etc. are provided



70+ Software Features

With over 70+ software features provides a best GPS tracking platform



Vehicle Stop / Start

With immobilization feature vehicle can be stopped and start remotely



Web and Mobile Platform

Web and mobile platform are available for user convenience



Multi Language Support

Support for multiple languages commonly spoken across the nation



Multiple Alerts

Supports multiple alerts like Ignition ON/OFF, Overspeed, Device Unplug, Movement, etc.



Geo-Fencing

Get instant alerts when vehicle enters or exits a specified boundary





| GSM Specification | | |
|---------------------|--------------------------------------|------------------------|
| GSM frequency | 850/900/1800/1900 MHz | |
| GPRS | Class12, TCP/ IP build in GSM Module | |
| Memory | 32+32Mb | |
| Phase error | RMSPE<5,PPE<20 | |
| Max output | GSM850/GSM900:33±3dBm | GSM1800/GSM1900:30±3Bm |
| Max frequency error | ±0.1ppm | |

| GPS Specification | | |
|-------------------------|---|--|
| GPS chipset | MTK high sensitivity chip | |
| Frequency | L1,1575.42MHz C/A code | |
| GPS channel | 66 | |
| Location accuracy | <10 meters | |
| Tracking sensitivity | -165dBm | |
| Acquisition sensitivity | -148dBm | |
| TTFF (open sky) | Avg. hot start≤1sec Avg. cold start≤32sec | |

| Other Details | | |
|-------------------------|--------------------------------|--|
| Battery | 270mAh/3.7V Li-Polymer battery | |
| Working voltage/current | 9-90VDC/7mA (60VDC) | |
| Operating temperature | -20°C ~ 70°C | |
| Standby time | 60 hours | |
| Working time | 3 hours | |
| Device weight | 38g | |
| Device dimension | 78.0(L)*41.0(W)*13.0(H)mm | |
| Box weight | 190g | |
| Box dimension | 123(L)*85(W)*49(H)mm | |
| | | |





Device Images




Application







Certificate Sample







Our Branches

Head Office:

Door No. 239/6 (1st Floor), Gandhi Road, Kakkan St, Tambaram West, Chennai, Tamil Nadu - 600045 North Chennai Office:

Karunanidhi Nagar, Vinobha Nagar, Old Washermanpet, Chennai, Tamil Nadu - 600118 Trichy Office

No. 33, Aattukara Street, Palakarai, Sangillyandapuram, Tiruchirappalli, Tamil Nadu -

620001

Madurai Office:

Plot No, No. 10, Ambika College Complex, 212, Anna Nagar Main Road, Madurai, Tamil Nadu 625020 **Coimbatore Office:**

3305,perumal kovil street Gandhima nagar, Coimbatore, Tamil Nadu - 641004 **Hosur Office:**

No. 2/705.6 Kadavul Nagar, Sanasandiram, Hosur,

Vellore Office:

No.13, Kaji Street, Pernambut, Gudiyattam Tk, Vellore Dt, TN 635810 **Perambalur Office:**

No. 174E A, Vadakku Theru 2, New Colony, Thoramangalam, Kanniyakumari Office:

No.15/157, Oorali Vilai Pacode, Vilavancode, Anducode, Kanniyakumari,

TN 629168

Chengalpet Office:

No. 03, Periyar Ramasamy Street, Guduvanchery, Chengalpet Dt, TN 603202

